



PROJECTEUR MURAL LED 50W

PR50WMCEE - 3700 619 436 159



IP65

ULR

< 3%



CONS : 50W



4500 LM

90lm/w

Efficacité lumineuse

LED

SOURCE REMPLACABLE



230V~50Hz



3000K



90°



ORIENTABLE



5M



CLASS I

165 x191
x26mm

IRC

>80

IK

8

CE

Conforme à l'arrêté du 27 décembre 2018 relatif à la prévention, à la réduction des nuisances lumineuses

Cerf/Test report	Directive	Normes
EMC	2014/30/EU	<ul style="list-style-type: none"> EN IEC 55015 : 2019 + A11 : 2020 EN IEC 61000-3-2 : 2019 EN 61000-3-3 : 2013 + A1 : 2019 EN 61547 : 2009
LVD	2014/35/EU	<ul style="list-style-type: none"> EN IEC 60598-1 : 2021 EN 60598-2-5:2015 EN62493:2015 EN 62471:2008
RoHS	2011/65/EU	

Facteur de puissance > 0.9
 Durée de vie : 25 000H
 3000K – Blanc CHAUD
 Source lumineuse remplaçable
 Aluminium / PC cover

Pour un ULR conforme à l'arrêté il convient de ne pas dépasser une inclinaison de 25° par rapport à l'horizontale

CEE Fiches : RES-EC-104 (A14-1) prorogée depuis 2021 Dec.
 Rénovation d'éclairage extérieur